







Hochdruck-Reinigungs-Schlauch High Pressure Cleaning Hose

**1 STC Kompakt mit 1 Drahtgeflechteinlage
 mit dicker Außendecke**
**1 STC Compact version with one layer of
 steel braiding with thick cover**

|  Nennweite Nominal |  Schlauch I. D. Hose I. D. | |  Schlauch A. D. Hose O. D. (MAX.) | |  Betriebsdruck Working Pressure (MAX. Dyn.) | |  Berstdruck Burst Pressure (MIN.) | |  Biegeradius Bend Radius (MIN.) | |
|---|---|-------|---|------|---|------|---|-------|---|-----|
| | DN | mm | in | mm | in | bar | psi | bar | psi | mm |
| 06 | 6,5 | 1/4" | 14,5 | 0,57 | 315 | 4568 | 1260 | 18272 | 75 | 3,0 |
| 08 | 8,1 | 5/16" | 17,0 | 0,67 | 315 | 4568 | 1260 | 18272 | 85 | 3,4 |

Aufbau:

Innenseele aus synthetischem Gummi, hochtemperaturbeständig und gegen handelsübliche Waschmittel beständig.
 1 Stahlgeflechteinlage.
 Außendecke aus synthetischem Gummi, abrieb-, öl-, ozon- und wetterbeständig, in dicker Ausführung.

Construction:

Inner tube out of synthetic rubber, resistant to high temperatures and detergent fluids.
 Reinforcement: 1 Braid of high tensile steel wire.
 Cover out of synthetic rubber, resistant to abrasion, oil, ozone, weathering, in thick version.

Anwendung:

Für Halb- und Profi-Waschgerätschaften bis 315 bar Betriebsdruck.

Application:

Hose range designed for semi professional and professional water cleaner applications up to 315 bar.

Farbe: Schwarz

Colour: Black

Auch in blau lieferbar.

Cover also is possible in colour blue.